

STEALTH[®]

AWARD METALS

Metal Products For The Construction Industry

www.awardmetals.com

ICC Evaluation: ER-5463

DADE COUNTY TESTED TO 80 M.P.H.

CALL FOR MORE INFORMATION

Finally!

An ICC Approved Metal Attic Vent

14 REASONS You Need STEALTH[®]



24" STEALTH[®] Vent

48" STEALTH[®] Vent

Available In

Paint-ready aluminum zinc
Pre-painted AWARD Colors
AWARD *STONECOAT*[™]

Four Widths

24", 30", 36", 48"

Deck Opening Sizes

24" = 14" x 5" 36" = 26" x 5"
30" = 20" x 5" 48" = 38" x 5"

Net Free Air Flow

24" = 40 sq. in. 36" = 66 sq. in.
30" = 53 sq. in. 48" = 90 sq. in.

* Net Free Air Flow calculated as follows:
Perforated area: 3/16" diameter holes .09375 radius
.09375 x 3.1416 = .0276115 sq. in. free area per hole

◆ DADE COUNTY TESTED!

For wind and wind driven rain resistance to 80 m.p.h.
under an 8.8" per hour rainstorm. Test: PA 100 (A-95)

◆ ICC Evaluation: ER-5463

- ◆ Low Cost
- ◆ Low profile design
- ◆ Easy to install - new construction or retrofit
- ◆ Can be used with all roofing materials including composition shingles, Flat or "S" tile roofs
- ◆ Available in paint-ready aluminum-zinc, pre-painted AWARD colors and *AWARD STONECOAT*[™]
- ◆ 4 sizes to choose from:
 - 24" with a 70 sq. in. opening and 40 sq. inches of net free air
 - 30" with a 100 sq. in. opening and 53 sq. inches of net free air
 - 36" with a 130 sq. in. opening and 66 sq. inches of net free air
 - 48" with a 190 sq. in. opening and 90 sq. inches of net free air
- ◆ No place for birds to nest
- ◆ No penetrations in eaves or gables
- ◆ No insulation baffles required
- ◆ Eliminates costly screened blocks
- ◆ Eliminates unsightly stains from downward airflow
- ◆ One of the most efficient attic "breathing" systems available

AWARD METALS

Metal Products For The Construction Industry